


Methods for the specification and verification of business processes

MPB (6 cfu, 295AA)

Roberto Bruni


<http://www.di.unipi.it/~bruni>

23 - Yet another workflow language



Object

We overview the key features of YAWL and the main differences with Petri nets



Some deficiencies

About **synchronization patterns**

Petri nets have difficulties in dealing with or-join patterns especially, synchronization merge, discriminator

Examples:

optional booking of flight, train, hotel, rental car, show tickets

number of paper submissions to a conference

Some deficiencies

About **multiple instances**

Petri nets do not provide adequate means to easily describe multiple instances tasks

Examples:

witness statements in processing insurance claim

number of paper submissions to a conference

Some deficiencies

About **nonlocal firing behaviour**

Petri nets do not provide adequate means
to model cancellation patterns
(the firing of a transition should atomically trigger the
cancellation of other tokens in some places,
if there are some tokens there)

Examples:
abort of a commercial transaction

A wish list

Graphical language

Formal syntax

Rigorous theory

Direct support for (all?) workflow patterns

Tool support

YAWL

Extended workflow net

Some transitions are labelled as AND/XOR/OR split


Some transitions are labelled as AND/XOR/OR join

Some transitions are assigned a set of places
to vacuum-clean when firing

Some transitions are assigned a (min, max, threshold)
number of multiple instances to be spawn
(statically or dynamically)


Transitions can be connected directly to transitions

Notational elements of YAWL




M. Weske: Business Process Management,
© Springer-Verlag Berlin Heidelberg 2007

Discriminator (via cancellation region)




N-out-of-M (via multiple instances)

(N-out-of-M of the same activity)



M. Weske: Business Process Management,
© Springer-Verlag Berlin Heidelberg 2007

Multiples instances without synchronization



M. Weske: Business Process Management,
© Springer-Verlag Berlin Heidelberg 2007

Expressiveness...
not in the formal sense
(w.r.t. WF patterns)

pattern	product							
	Staffware	COSA	InConcert	Eastman	FLOWer	Domino	Meteor	Mobile
1 (seq)	+	+	+	+	+	+	+	+
2 (par-spl)	+	+	+	+	+	+	+	+
3 (synch)	+	+	+	+	+	+	+	+
4 (ex-ch)	+	+	+/-	+	+	+	+	+
5 (simple-m)	+	+	+/-	+	+	+	+	+
6 (m-choice)	-	+	+/-	+/-	-	+	+	+
7 (sync-m)	-	+/-	+	+	-	+	-	-
8 (multi-m)	-	-	-	+	+/-	+/-	+	-
9 (disc)	-	-	-	+	+/-	-	+/-	+
10 (arb-c)	+	+	-	+	-	+	+	-
11 (impl-t)	+	-	+	+	-	+	-	-
12 (mi-no-s)	-	+/-	-	+	+	+/-	+	-
13 (mi-dt)	+	+	+	+	+	+	+	+
14 (mi-rt)	-	-	-	-	+	-	-	-
15 (mi-no)	-	-	-	-	+	-	-	-
16 (def-c)	-	+	-	-	+/-	-	-	-
17 (int-par)	-	+	-	-	+/-	-	-	+
18 (milest)	-	+	-	-	+/-	-	-	-
19 (can-a)	+	+	-	-	+/-	-	-	-
20 (can-c)	-	-	-	-	+/-	+	-	-

pattern	product						
	MQSeries	Forté	Verve	Vis. WF	Changeng.	I-Flow	SAP/R3
1 (seq)	+	+	+	+	+	+	+
2 (par-spl)	+	+	+	+	+	+	+
3 (synch)	+	+	+	+	+	+	+
4 (ex-ch)	+	+	+	+	+	+	+
5 (simple-m)	+	+	+	+	+	+	+
6 (m-choice)	+	+	+	+	+	+	+
7 (sync-m)	+	-	-	-	-	-	-
8 (multi-m)	-	+	+	-	-	-	-
9 (disc)	-	+	+	-	+	-	+
10 (arb-c)	-	+	+	+/-	+	+	-
11 (impl-t)	+	-	-	-	-	-	-
12 (mi-no-s)	-	+	+	+	-	+	-
13 (mi-dt)	+	+	+	+	+	+	+
14 (mi-rt)	-	-	-	-	-	-	+/-
15 (mi-no)	-	-	-	-	-	-	-
16 (def-c)	-	-	-	-	-	-	-
17 (int-par)	-	-	-	-	-	-	-
18 (milest)	-	-	-	-	-	-	-
19 (can-a)	-	-	-	-	-	-	+
20 (can-c)	-	+	+	-	+	-	+

<i>pattern</i>	<i>standard</i>				
	BPEL	XLANG	WSFL	BPML	WSCI
Sequence	+	+	+	+	+
Parallel Split	+	+	+	+	+
Synchronization	+	+	+	+	+
Exclusive Choice	+	+	+	+	+
Simple Merge	+	+	+	+	+
Multi Choice	+	-	+	-	-
Synchronizing Merge	+	-	+	-	-
Multi Merge	-	-	-	+/-	+/-
Discriminator	-	-	-	-	-
Arbitrary Cycles	-	-	-	-	-
Implicit Termination	+	-	+	+	+
MI without Synchronization	+	+	+	+	+
MI with a Priori Design Time Knowledge	+	+	+	+	+
MI with a Priori Runtime Knowledge	-	-	-	-	-
MI without a Priori Runtime Knowledge	-	-	-	-	-
Deferred Choice	+	+	-	+	+
Interleaved Parallel Routing	+/-	-	-	-	-
Milestone	-	-	-	-	-
Cancel Activity	+	+	+	+	+
Cancel Case	+	+	+	+	+

pattern	YAWL
1 (seq)	+
2 (par-spl)	+
3 (synch)	+
4 (ex-ch)	+
5 (simple-m)	+
6 (m-choice)	+
7 (sync-m)	+
8 (multi-m)	+
9 (disc)	+
10 (arb-c)	+
11 (impl-t)	— (<i>iv</i>)
12 (mi-no-s)	+
13 (mi-dt)	+
14 (mi-rt)	+
15 (mi-no)	+
16 (def-c)	+
17 (int-par)	+
18 (milest)	+
19 (can-a)	+
20 (can-c)	+

- (i) The synchronizing merge is not supported because the designer has to keep track of the number of parallel threads and decide to merge or synchronize flows (cf. Section 3.2).
- (ii) The discriminator is not supported because the designer needs to keep track of the number of threads running and the number of threads completed and has to reset the construct explicitly by removing all tokens corresponding to the iteration (cf. Section 3.2).
- (iii) Implicit termination is not supported because the designer has to keep track of running threads to decide whether the case is completed. **(about YAWL)**
- (iv) Implicit termination is not supported because the designer is forced to identify one unique final node. Any model with multiple end nodes can be transformed into a net with a unique end node (simply use a synchronizing merge). This has not been added to YAWL to force the designer to think about successful completion of the case. This requirement allows for the detection of unsuccessful completion (e.g., deadlocks).
- (v) Multiple instances with synchronization are not supported by high-level Petri nets (cf. Section 3.1).
- (vi) Also not supported, cf. Section 3.1.
- (vii) Cancel activity is only partially supported since one can remove tokens from the input place of a transition but additional bookkeeping is required if there are multiple input places and these places may be empty (cf. Section 3.3).
- (viii) Cancel activity is not supported because one needs to model a vacuum clearer to remove tokens which may or may not reside in specific places (cf. Section 3.3).

Advantages and drawbacks

Graphical presentation closely related to WF nets

Formal semantics (state- transitions model)

Support for Multiple Instance patterns

Support for cancellation region

Unfortunately **soundness properties are undecidable**
when reset arcs are used

But you can still play with YAWL by downloading it from

<http://www.yawlfoundation.org/>